

**MACARON** LED ACCENT LIGHT




**Macaron**  
DDC-65380 Series






HOOD - A





HOOD - B



OPTION A  
GLASS  
: WIDE BEAM




OPTION B  
GLASS  
: OVAL BEAM



OPTION C  
LOUVER  
: HONEY COMB



# Macaron



**DDC-65380 SERIES** NEW

- DDC-65380 COB 18 W
- DDC-65381 COB 27 W

Track Accent Light

TYPE OF LED : COB



**LED HOUSING & HEAT SINK**  
AL. Die-Casting, Electrostatic Powder Coating  
Adjustable Angle (Tilt  $\pm 90^\circ$ )

**REFLECTOR LENS**

**MOUNTING RING**  
AL. Extrude, Electrostatic Powder Coating

**INSTALLATION**  
On 1 or 3 circuit track (PC)

TYPE OF LED		COB						
INPUT VOLTAGE		220-240 Vac , 50/60 Hz						
INPUT POWER	OUTPUT POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	CRI	COLOR TEMPERATURE	BEAM ANGLE	LUMINOUS FLUX	
<b>DDC-65380</b>								
18 W	17 W	34 Vdc	500 mA	80	3 000 K	17.8 °	1 912 lm	
						27.7 °	1 907 lm	
						43.8 °	2 021 lm	
<b>DDC-65381</b>								
27 W	24 W	35 Vdc	700 mA	80	3 000 K	18.2 °	2 527 lm	
						27.7 °	2 599 lm	
						43.4 °	2 649 lm	

- OPERATING TEMPERATURE RANGE -20 to +40 °C
- MAINTENANCE OF LUMEN -L80 50 000 hours at 25 °C
- COLOR RENDERING INDEX 80, 90
- COLOR TEMPERATURE 4 000 K / 3 000 K

**CCT MULTIPLIERS**

	CRI 80	CRI 90
3 000 K	x 1.00	x 0.85
4 000 K	x 1.06	x 0.91

